**SPREAD SPECTRUM BURST SIGNAL
RECEIVER AND RELATED METHODS**

Related Application

The present application is based upon co-pending provisional application serial no. 60/177,201 filed January 21, 2000, which is hereby incorporated
5   herein in its entirety by reference.

Field of the Invention

The present invention relates to the field of telecommunications, and, more particularly, to a spread
10   spectrum communication receiver and related methods.

Background of the Invention

Spread spectrum communications systems are well known in the art. These systems differ from
15   traditional radio systems, such as amplitude modulation (AM) and frequency modulation (FM) systems, in that the signal being transmitted is spread over a wide bandwidth rather than being centered around a particular carrier frequency. As a result, spread
20   spectrum signals are less susceptible to either cause interference with or be affected by interference from such traditional radio transmissions.

Burst mode communication is another class of communications that is useful in a number of

applications. A burst mode transmission involves
sending data at a faster rate than normal for a limited
period of time. One particular application where burst
mode transmissions are beneficial is in wireless
5   location devices. The low duty cycle, short duration
transmission sequences allow for power conservation and
higher system capacities through minimizing on air
time.

Combining burst mode protocols with spread
10 spectrum transmissions may provide even further
reduction in interference with other signals. One
example of a spread spectrum system which uses burst
mode transmissions is provided in U.S. Patent No.
5,717,713 to Natali entitled "Technique to Permit Rapid
15 Acquisition and Alert Channel Signaling for Base
Station-to-User Link of an Orthogonal CDMA (OCDMA)
Communication System." This patent discloses a spread
spectrum receiver including amplifiers and in-phase (I)
and quadrature (Q) mixers for down converting a
20 received signal to a baseband. The signal is then
routed to a digital matched filter. An output of the
digital matched filter is monitored for correlation
peaks that indicate signal presence. If the receiver
is tuned to a proper frequency, an AC burst signal will
25 be detected by a signal presence detector. Otherwise,
the receiver keeps searching until the signal is
detected.

While such a burst mode spread spectrum
system may provide reduced interference with respect to
30 many transmissions, it may still be susceptible to
interference from other sources. These sources may
include narrow band data communication systems such as
frequency hopping wireless local area networks (LANs),
for example. As a result, when interference from such
35 a system is present, a spread spectrum receiver will be

more susceptible to false acquisition detections of the spread spectrum burst signal.

Summary of the Invention

5   In view of the foregoing background, it is therefore an object of the invention to provide a receiver for a spread spectrum burst signal and related methods for reducing false acquisition detections of the spread spectrum burst signal.

10   This and other objects, features, and advantages in accordance with the present invention are provided by a receiver for a spread spectrum burst signal having a predetermined period including a time invariant matched filter for comparing an input signal

15   to at least one reference signal based upon a pseudo-noise (PN) code and providing a stream of data values and a threshold comparator for comparing each of the stream of data values to a threshold to determine an acquisition time for the spread spectrum burst signal.

20   The receiver may further include a contrast filter connected between the time invariant matched filter and the threshold comparator for varying the threshold based upon an interference level to reduce instances of false acquisition detections. Additionally, the

25   receiver may include a window sampler for selectively sampling the data values based upon the acquisition time and the predetermined period.

More specifically, the contrast filter may subtract a weighted average of a current and previous

30   data values from the current data value. The contrast filter may include a plurality of delay registers connected in series and each providing an output, and a summer for summing the outputs from the plurality of delay registers.

Additionally, the input signal may include in-phase (I) and quadrature (Q) values, and the time invariant matched filter may compare the I and Q values of the input signal to I and Q values of the at least
5 one reference signal to provide a stream of I and Q data values. A magnitude converter may also be connected between the time invariant matched filter and the contrast filter for converting I and Q data values into a magnitude data value.

10 The receiver may further include a counter connected to the threshold comparator for generating an acquisition count based upon the acquisition time. Moreover, a window controller may be connected to the counter for generating a window strobe signal for
15 controlling the window sampler. The receiver may also include a memory connected to the window sampler for storing the data values and a processor connected to the memory for processing the stored data values. More specifically, the memory may be a first-in first-out
20 (FIFO) memory, and the processor may be a digital signal processor. The processor preferably performs non-real time processing of the stored data values.

Furthermore, the time invariant matched filter may continuously search over at least one of
25 time, frequency, phase, and PN code alignments. The time invariant matched filter may include a discrete time, discrete amplitude device implementing a complex arithmetic cross correlation function. Further, the stream of data values may include a complex stream of
30 data values based upon a degree and phase of correlation between the input signal and the at least one reference signal.

The receiver may further include a down converter upstream from the time invariant matched
35 filter and a low noise amplifier upstream from the down

converter. An analog-to-digital (A/D) converter may also be upstream from the time invariant matched filter.

A method aspect of the invention for receiving a spread spectrum burst signal having a predetermined period includes comparing an input signal to at least one reference signal based upon a PN code and providing a stream of data values, and comparing each of the stream of data values to a threshold to determine an acquisition time for the spread spectrum burst signal. The threshold may be varied based upon an interference level to reduce instances of false acquisition detections.

Another method aspect of the invention for receiving a spread spectrum burst signal having a predetermined period includes comparing an input signal to at least one reference signal based upon a PN code and a stream of data values and comparing each of the stream of data values to a threshold to determine an acquisition time for the spread spectrum burst signal. Furthermore, the data values may be selectively sampled based upon the acquisition time and the predetermined period.

Yet another method aspect of the invention for receiving a spread spectrum burst signal having a predetermined period includes comparing an input signal to at least one reference signal based upon a pseudo-noise (PN) code and providing a complex stream of data values based upon a degree and phase of correlation between the input signal and the at least one reference signal. Additionally, each of the data values is compared to a threshold to determine an acquisition time for the spread spectrum burst signal

Brief Description of the Drawings

FIG. 1 is a schematic block diagram of a receiver for a spread spectrum burst signal according to the present invention.

5   FIG. 2 is a more detailed schematic block diagram of the time invariant matched filter of FIG. 1.

FIG. 3 is a more detailed schematic block diagram of the magnitude converter of FIG. 1.

10   FIG. 4 is a more detailed schematic block diagram of the contrast filter of FIG. 1.

FIG. 5 is a more detailed schematic block diagram of the acquisition detector of FIG. 1.

FIG. 6 is a more detailed schematic block diagram of the window sampler of FIG. 1.

15   FIG. 7 is a more detailed schematic block diagram of the window controller of FIG. 1.

FIG. 8 is a more detailed schematic block diagram of the time tag counter of FIG. 1.

Detailed Description of the Preferred Embodiments

20   The present invention will now be described more fully hereinafter with reference to the accompanying drawings, in which preferred embodiments of the invention are shown. This invention may,

25   however, be embodied in many different forms and should not be construed as limited to the embodiments set forth herein. Rather, these embodiments are provided so that this disclosure will be thorough and complete, and will fully convey the scope of the invention to

30   those skilled in the art. Like numbers refer to like elements throughout.

Referring now to the schematic block diagrams of FIGS. 1 to 8, a receiver 20 for a spread spectrum burst signal having a predetermined period in

35   accordance with the present invention is now described.

The receiver **20** may be used with a transmitter **21** which transmits a spread spectrum burst signal via an antenna **22**. The transmitter **21** and receiver **20** are particularly well suited for wireless location devices,

5   such as the WalkMate locator system manufactured by Microgistics, Inc. of Melbourne, Florida. The transmitter **21** and receiver **20** preferably operate using the direct sequence spread spectrum protocol, as will be understood by those of skill in the art. However,

10 other spread spectrum protocols, such as frequency hopping, which are also known to those skilled in the art may also be used.

The receiver **20** includes an antenna **23** for receiving input signals. A low noise amplifier (LNA)

15 and down converter **22** (illustratively shown as a single element for convenience) preferably covert the received input signal into analog in-phase (I) and quadrature (Q) values, for example, which may be done in a conventional manner known to those of skill in the art.

20 Of course, it will also appreciate that other signal formats may be used in accordance with the present invention. The analog I and Q values are then converted into digital I and Q values by an analog-to-digital (A/D) converter **23**.

25 The A/D converter **23** and LNA/down converter **22** are upstream from a time invariant matched filter **24**. The time invariant matched filter **24** compares the digital I and Q values of the input signal to I and Q values of at least one reference signal based upon a

30 pseudo-noise (PN) code and provides a stream of I and Q data values. To this end, the time invariant matched filter **24** includes multiplication paths **35a-35d**, as shown in FIG. 2. Each multiplication path includes a respective N bit data delay register **36a-36d, 37a-37d**

for the I and Q values being received from the A/D
converter **23**. The registers **36a-36d, 37a-37d** may be
serial registers, for example. While four
multiplication paths **35a-35d** are shown in FIG. 2, those
5 skilled in the art will appreciate that other numbers
of multiplication paths may be used depending upon the
desired accuracy to be achieved.

Each multiplication path **35a-35d** further
includes a respective complex multiplier **38a-38d** which
10 multiplies respective outputs from the registers **36a-
36d, 37a-37d** with data stored in reference registers
39a-39d, 40a-40d corresponding to I and Q values of the
at least one reference signal. I and Q outputs from
the complex multipliers **38a-38d** are input to respective
15 Wallace tree adders **41a-41d**. Furthermore, respective I
and Q outputs from each of the Wallace tree adders **41**
are input to phase shifters **42-47** corresponding to each
respective multiplication path **35a-35d**. Each phase
shifter **42-47** shifts its respective inputs by different
20 amounts depending upon a target frequency for each
summer **48-53**. The summers **48-53** sum respective outputs
of the phase shifters **42-47** to provide a complex stream
of I and Q data values based upon a degree and phase of
correlation between the input signal and the at least
25 one reference signal.

It will therefore be appreciated by those of
skill in the art that the time invariant matched filter
24 is a discrete time, discrete amplitude device
implementing a complex arithmetic cross correlation
30 function. The time invariant matched filter **24**
continuously searches over at least one of time,
frequency, phase, and PN code alignments to provide for
a substantially instantaneous acquisition of the spread
spectrum burst signal. Thus, the time invariant

matched filter **24** according to the present invention overcomes many of the difficulties associated with traditional acquisition and tracking loops of burst communication systems, as will also be appreciated by
5 those of skill in the art.

The receiver **20** further includes a magnitude converter **25** connected between the time invariant matched filter **24** and a contrast filter **26**. The magnitude converter **25** converts the I and Q stream of
10 data values from the time invariant matched filter **24** into a stream of magnitude data values. For example, the magnitude converter may be implemented using a circuit **54** which takes the square root of the sum of the squares of each pair of corresponding I and Q data
15 values, as shown in FIG. 3.

The contrast filter **26** is connected between the magnitude converter **25** and a threshold comparator **27**. The threshold comparator **27** compares each of the magnitude data values to a threshold to determine an
20 acquisition time for the spread spectrum burst signal. The threshold comparator **27** includes a magnitude comparator **60** for comparing filtered magnitude data values from the contrast filter **26** to the threshold, which is stored in a register **61**, as shown in FIG. 5.
25 An acquisition detect signal ACQ Detect is output by the threshold comparator **27** to indicate an acquisition detection of the spread spectrum burst signal.

Prior art acquisition tracking loops typically use a fixed or static threshold. Yet, if
30 interfering signals or ambient noise is present then a probability of acquiring the spread spectrum burst signal is decreased. For example, such interference may cause a variation of the time invariant matched

filter **24** gain, which would increase the chance of a
false acquisition detection using prior art methods.

   According to the present invention, the
contrast filter **26** causes the threshold stored in the
5   threshold register **61** to be varied based upon an
interference level (e.g., ambient noise) to reduce
instances of false acquisition detections. By using a
varying or dynamic threshold that is adjusted based
upon interference received by the receiver **20,** the
10   acquisition detector is less susceptible to
interference from sources such as narrow band data
communication systems that may otherwise cause a low
probability of detection. Accordingly, the contrast
filter **26** allows the acquisition detector **27** to more
15   accurately detect acquisition of the spread spectrum
burst signal.

   The contrast filter **26** includes delay
registers **55a-55d** connected in series which receive the
magnitude data values from the magnitude converter **25**
20   and each provide a respective output, as may be seen in
FIG. 4. A summer **56** sums the outputs from the delay
registers **55.** An output of the summer **56** is connected
to a multiplier **57** for multiplication with a constant K
to provide a weighted average of a current and previous
25   data values. A subtraction element **58** subtracts the
weighted average from the current data value and
provides filtered magnitude data values to the
threshold comparator **27.**

   In addition to more accurately detecting
30   acquisition of the spread spectrum burst signal, the
present invention also provides for a significant
reduction in processing following the acquisition. To
this end, the receiver **20** includes a window sampler **28**
for selectively sampling the data values received from

the time invariant matched filter **24** based upon the
acquisition time determined by the acquisition detector
27 and the predetermined period of the spread spectrum
burst signal, which is known by the receiver. That is,

5 once the acquisition time is determined by the
acquisition detector **27**, the timing of future data
bursts can be determined using the acquisition time and
the predetermined period.

As a result, only the data values

10 corresponding to an expected time for each future data
burst need to be processed and the rest may be
discarded. Thus, by selectively sampling the data
values corresponding to each data burst, the window
sampler **28** provides a much smaller window of data

15 values to be processed. As may be seen in FIG. 6, the
window sampler includes a sample register **62** receiving
as inputs the stream of I and Q data values from the
time invariant matched filter **24**, a Time Tag Count
signal, and a Window Strobe signal on a clock input of

20 the sample register.

The time tag counter **29** includes a counter
69, which may be a free running counter driven by a
clock signal from a stable oscillator (not shown), for
example, as shown in FIG. 8. A register **68** is

25 connected to the counter **69** and receives as an input
the ACQ Detect signal. Upon detection of an
acquisition of the spread spectrum burst signal, the
ACQ Detect signal causes a current count value from the
counter **69** to be written on the register **68** and output

30 as a signal ACQ Count.

The ACQ Count signal is input to a register
27 of the window controller **30**, as seen in FIG. 7. A
controller **65** of the window controller **30** receives the
ACQ Detect signal indicating an acquisition detection

and generates the Window Strobe signal. The Window
Strobe signal causes the window sampler **28** to store a
window of data values for a short duration
corresponding to an expected data burst. For example,
5   the short duration may be a period corresponding to
four data values before and after an expected data
burst. In this way, slight timing drifts of the data
burst will not cause the data burst to be outside of
the window of data values. An adder connected to the
10   controller **65** and the register **67** provides the Time Tag
Count signal, which may be stored with the window of I
and Q data values for later processing, as seen in FIG.
6.

        Of course, by waiting until the ACQ Detect
15   signal is received to generate the Window Strobe
signal, at least one initial data value will not be
included within the window of data values. However, a
plurality of acquisition bursts are typically sent at
the beginning of a data burst sequence, so this will
20   likely not present a problem in many applications.
Nonetheless, an additional memory could be included
upstream from the window sampler **28** to store incoming
data values so that the first acquisition burst may be
included within each window if necessary, as will be
25   appreciated by those of skill in the art.

        A memory **31**, such as a first-in first-out
(FIFO) memory, is connected to the window sampler **28**
for storing the window of data values. A separate
window of data values may be stored for each symbol of
30   an incoming message, for example, and the windows
corresponding to a particular message may be stored as
separate blocks. A processor **32** is connected to the
memory **31** for processing the stored data values. The
processor **32** may be an asynchronous processor, for

example, such as a digital signal processor (DSP).
Additionally, a plurality of DSPs may be used to
improve throughput where each DSP processes a different
message block, for example, as will be appreciated by
5   those of skill in the art. It will also be appreciated
that the processor **32** may advantageously perform non-
real time processing of the stored data values.

Many of the above described elements, such as
the time invariant matched filter **24,** the magnitude
10 converter **25,** the contrast filter **26,** and the window
sampler **28,** for example, have been represented as
discrete elements for ease of illustration. However,
those of skill in the art will appreciate that such
elements may be implemented using software.
15 Furthermore, the receiver **30** according to the present
invention may be implemented using an application
specific integrated circuit (ASIC), for example.

Additionally, many modifications and other
embodiments of the invention will come to the mind of
20 one skilled in the art having the benefit of the
teachings presented in the foregoing descriptions and
the associated drawings. Therefore, it is to be
understood that the invention is not to be limited to
the specific embodiments disclosed, and that other
25 modifications and embodiments are intended to be
included within the scope of the appended claims.